

T303

TECHNICAL DATA SHEET

TECHNICAL INFORMATION

INOLUB™ T303 is a PTFE micropowder with discrete particles and good powder flow. It is primarily designed for use in paint, coating and ink applications, where it is used as an additive at concentrations in the range of 0.5-3.0.

PRODUCT FEATURES

- Improved non-stick performance and anti-friction properties
- Reduced blocking
- Improved abrasion, rub resistance and anti-scratching
- Discrete particles, providing minimal rheological impact

TYPICAL PROPERTIES

Properties	Test Method	Unit	Nominal Value
Appearance	-	-	White free flowing powder
Bulk density	ASTM D4894	g/l	250
Mean particle size (D50)	ASTM D4894	µm	3
Specific surface area	Nitrogen Adsorption	m ² /g	<3
Melting point	ASTM D4894	°C (°F)	325 (617)

Note: These are typical properties and not to be used for specification purposes.

TYPICAL END USE APPLICATIONS

INOLUB™ T303 has narrow particle size distribution which is well suited for use in offset inks to improve abrasion resistance, imparting non-stick properties that prevent the printed image from sticking. It can also be used in paints and thin coatings imparting rub, scuff and scratch resistance.

INOLUB™ T303

PACKAGING

INOLUB™ T303 is available in 12.5 kg corrugated boxes, packed in a polyethylene liner.

STORAGE

INOLUB™ T303 may be stored indefinitely, provided that the packaging remains unopened and that it has been stored in a clean and dry area at a temperature below 27°C (80°F).

SAFETY AND HANDLING

Although INOLUB™ T303 presents no safety hazard under normal handling conditions, please refer to the Material Safety Data Sheet to avoid potential hazards before processing.

INOLUB™ is the brand name of Gujarat Fluorochemicals Limited (GFL) used for its brand of fluoropolymer additives. INOLUB™ can be used in applications duly approved by GFL. Customers who plan to use the word INOLUB™ as the trademark on or relation to their manufactured parts and other products in any style or combination or any manner whatsoever must contact GFL for prior permission for such use. No consumer/user of GFL fluoropolymer additives is permitted to claim that their products contain INOLUB™ without prior permission from GFL.

The information provided in the bulletin is furnished at no cost to the recipient and is based on the information and technical data that Gujarat Fluorochemicals Limited believes is correct and sound. Those who choose to use the information must be technically qualified, and do so entirely at their own cost and risk. The users must determine and ensure that their specific conditions of processing present no health or safety hazards. GFL does not warranty, either expressly or impliedly in respect of the use of this information for application of its INOLUB™ branded fluoropolymer additives and shall bear no liability as a result of any loss or damage caused directly or indirectly due to use of any information provided in this bulletin. Nothing contained herein can be taken or construed as a grant of license by GFL to operate under or a recommendation to infringe any patents.

WARNING: Do not use any of INOLUB™ PTFE additives in medical devices that are designed for permanent implantation in the human body. For other medical uses, prior permission of GFL may be sought.

SALES AND TECHNICAL SUPPORT

Corporate & Marketing Headquarter

Gujarat Fluorochemicals Limited
INOX Towers, 17, Sector-16A,
Noida - 201301 U.P., India
+91 120 6149600

Europe

Gujarat Fluorochemicals GmbH
Regus Center Watermark 14th Floor,
Überseeallee 10, 20457 Hamburg, Germany
+49 40 808074-667/668

Works

Gujarat Fluorochemicals Limited
12/A Dahej, GIDC, Industrial Estate,
Tehsil Vagra, Dist. Bharuch 392130, Gujarat, India
+91 2641 618003

Americas

GFL Americas, LLC
1212 Corporate Dr., Suite-540,
Irving, TX 75038, USA
+1 512 446 7700

