

# PTFE Additive Powder

Gujarat Fluorochemicals Ltd.

Version No: 2.2

Safety Data Sheet (Conforms to Regulation (EU) No 2015/830)

Chemwatch Hazard Alert Code: 0

Issue Date: 22/06/2018 Print Date: 23/08/2018 S.REACH.GBR.EN

# SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

#### 1.1. Product Identifier

| Product name                  | PTFE Additive Powder                                  |
|-------------------------------|---|
| Chemical Name                 | polyte trafluoroe thyle ne                            |
| Synonyms                      | INOLUB™ T100, 200, 300 SERIES. R 600, 700, 800 SERIES |
| Chemical formula              | $(C_2F_4)_x$  |
| Other means of identification | Not Available   |
| CAS number                    | 9002-84-0*  |

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

| Relevant identified uses | Addtive        |
|--------------------------|----------------|
| Uses advised against     | Not Applicable |

#### 1.3. Details of the supplier of the safety data sheet

| Registered company name | Gujarat Fluorochemicals Ltd.             |
|-------------------------|--|
| Address                 | 12/A, GIDC Dahej Industrial Estate India |
| Telephone               | +91-2641-618333                          |
| Fax                     | +91-2641-618012                          |
| Website                 | www.inolub.com                           |
| Email                   | inolub@gfl.co.in                         |

# 1.4. Emergency telephone number

| Association / Organisation        | Gujarat Fluorochemicals ltd |
|-----------------------------------|-----------------------------|
| Emergency telephone numbers       | +91-2641-618080-81          |
| Other emergency telephone numbers | Not Available               |

# SECTION 2 HAZARDS IDENTIFICATION

#### 2.1. Classification of the substance or mixture

Not considered a hazardous substance according to Reg. (EC) No 1272/2008 and its amendments. Not classified as Dangerous Goods for transport purposes.

#### CHEMWATCH HAZARD RATINGS

|              | Min | Max |                         |
|--------------|-----|-----|-------------------------|
| Flammability | 0   |     |                         |
| Toxicity     | 0   |     | 0 = Minimum             |
| Body Contact | 0   |     | 1 = Low<br>2 = Moderate |
| Reactivity   | 0   |     | 3 = High                |
| Chronic      | 0   |     | 4 = Extreme             |

| Classification according to                 |
|---|
| regulation (EC) No 1272/2008 Not Applicable |

#### 2.2. Label elements

| 2.2. Label elements |                |  |
|---------------------|----------------|--|
| Hazard pictogram(s) | Not Applicable |  |
|                     |                |  |
|                     | NOT APPLICABLE |  |

Hazard statement(s)

Not Applicable

Supplementary statement(s)

Not Applicable

Page 2 of 10 Issue Date: 22/06/2018 Chemwatch: 9-553968 Print Date: 23/08/2018 Version No: 2.2

#### PTFE Additive Powder

Precautionary statement(s) Prevention

Not Applicable

Precautionary statement(s) Response

Not Applicable

Precautionary statement(s) Storage

Not Applicable

Precautionary statement(s) Disposal

Not Applicable

#### 2.3. Other hazards

Cumulative effects may result following exposure\*.

Limited evidence of a carcinogenic effect\*.

 $REACh - Art. 57-59: The \ mixture \ does \ not \ contain \ Substances \ of \ Very \ High \ Concern \ (SVHC) \ at \ the \ SDS \ print \ date.$ 

▶ Elevate feet about 12 inches.

# SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

#### 3.1.Substances

| 1.CAS No<br>2.EC No<br>3.Index No<br>4.REACH No                      | %[weight] | Name                     | Classification according to regulation (EC) No 1272/2008 [CLP] |
|--|-----------|--------------------------|--|
| 1.9002-84-0<br>2.Not Available<br>3.Not Available<br>4.Not Available | >99.9     | polytetrafluoroethyle ne | Not Applicable   |

1. Classified by Chemwatch; 2. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 3. Classification drawn from C&L; \*EU IOELVs available Legend:

#### 3.2.Mixtures

See 'Information on ingredients' in section 3.1

# SECTION 4 FIRST AID MEASURES

|              | If this product comes in contact with eyes:  |
|--------------|--|
|              | ▶ Wash out immediately with water.   |
|              | If irritation continues, seek medical attention.   |
|              | Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.  |
| Eye Contact  | For THERMAL burns:   |
| ,            | ▶ Do not remove contact lens   |
|              | Lay victim down, on stretcher if available and pad BOTH eyes, make sure dressing does not press on the injured eye by placing                    |
|              | thick pads under dressing, above and below the eye.  |
|              | ▶ Seek urgent medical assistance, or transport to hospital.  |
|              | If skin or hair contact occurs:  |
|              | Flush skin and hair with running water (and soap if available).  |
|              | Seek medical attention in event of irritation.   |
|              | In case of burns:  |
|              | ► Immediately apply cold water to burn either by immersion or wrapping with saturated clean cloth.   |
|              | ▶ Do not remove or cut away chithing over burnt areas. DO NOT pull away chithing which has adhered to the skin as this can cause further injury. |
|              | ▶ Do not break blister or remove solidified material.  |
|              | Quickly cover wound with dressing or clean cloth to help prevent infection and to ease pain.   |
|              | For large burns, sheets, towels or pillow slips are ideal; leave holes for eyes, nose and mouth.   |
|              | Do not apply ointments, oils, butter, etc. to a burn under any circumstances.  |
|              | • Water may be given in small quantities if the person is conscious.   |
|              | Alcohol is not to be given under any circumstances.  |
|              | ▶ Reassure.  |
|              | ▶ Treat for shock by keeping the person warm and in a lying position.  |
|              | Seek medical aid and advise medical personnel in advance of the cause and extent of the injury and the estimated time of arrival of the patient. |
|              | For thermal burns:   |
| Skin Contact | ▶ Decontaminate area around burn.  |
|              | Consider the use of cold packs and topical antibiotics.  |
|              | For first-degree burns (affecting top layer of skin)   |
|              | ▶ Hold burned skin under cool (not cold) running water or immerse in cool water until pain subsides.   |
|              | ▶ Use compresses if running water is not available.  |
|              | ▶ Cover with sterile non-adhesive bandage or clean cloth.  |
|              | ▶ Do NOT apply butter or ointments; this may cause infection.  |
|              | Give over-the counter pain relievers if pain increases or swelling, redness, fever occur.  |
|              | For second-degree burns (affecting top two layers of skin)   |
|              | ▶ Cool the burn by immerse in cold running water for 10-15 minutes.  |
|              | ▶ Use compresses if running water is not available.  |
|              | ▶ Do NOT apply ice as this may lower body temperature and cause further damage.  |
|              | ▶ Do NOT break blisters or apply butter or ointments; this may cause infection.  |
|              | Protect burn by cover loosely with sterile, nonstick bandage and secure in place with gauze or tape.   |
|              | To prevent shock: (unless the person has a head, neck, or leg injury, or it would cause discomfort):   |
|              | ▶ Lay the person flat.   |

Chemwatch: 9-553968 Page 3 of 10 Is sue Date: 22/06/2018 Version No: 2.2 Print Date: 23/08/2018

#### PTFE Additive Powder

• Elevate burn area above heart level, if possible. · Cover the person with coat or blanket. ▶ Seek medical assistance. For third-degree burns Seek immediate medical or emergency assistance. In the mean time: ▶ Protect burn area cover loosely with sterile, nonstick bandage or, for large areas, a sheet or other material that will not leave lint in wound. • Separate burned toes and fingers with dry, sterile dressings. ▶ Do not soak burn in water or apply ointments or butter; this may cause infection. ▶ To prevent shock see above. For an airway burn, do not place pillow under the person's head when the person is lying down. This can close the airway. ▶ Have a person with a facial burn sit up. ▶ Check pulse and breathing to monitor for shock until emergency help arrives. ▶ If dust is inhaled, remove from contaminated area. • Encourage patient to blow nose to ensure clear breathing passages. Inhalation ▶ Ask patient to rinse mouth with water but to not drink water. • Seek immediate medical attention. ▶ Immediately give a glass of water. Ingestion First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.

4.2 Most important symptoms and effects, both acute and delayed

See Section 11

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

For polytetrafluoroethylene (PTFE) and other related polyfluorinated polymers:

Pyrolysis products of this material have been known to produce an influenza-like syndrome in man, lasting 24-48 hours. (ILO)

#### SECTION 5 FIREFIGHTING MEASURES

- 5.1. Extinguishing media
  - Do not direct a solid stream of water or foam into burning molten material; this may cause spattering and spread the fire.
  - Foam.
  - Dry chemical powder.
  - BCF (where regulations permit).
  - · Carbon dioxide.
- 5.2. Special hazards arising from the substrate or mixture

| TO T ATLANTA         | - No. 4 (1) - 2 (1) - 24 (1) - 12 (1) - 2 (1) |
|----------------------|---|
| Fire Incompatibility | Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result  |

#### 5.3. Advice for firefighters

| Fire Fighting         | <ul> <li>Alert Fire Brigade and tell them location and nature of hazard.</li> <li>Wear breathing apparatus plus protective gloves.</li> <li>Prevent, by any means available, spillage from entering drains or water courses.</li> <li>Use water delivered as a fine spray to control fire and cool adjacent area.</li> </ul>   |
|-----------------------|--|
| Fire/Explosion Hazard | <ul> <li>▶ Combustible solid which burns but propagates flame with difficulty; it is estimated that most organic dusts are combustible (circa 70%) - according to the circumstances under which the combustion process occurs, such materials may cause fires and / or dust explosions.</li> <li>▶ Organic powders when finely divided over a range of concentrations regardless of particulate size or shape and suspended in air or some other oxidizing medium may form explosive dust-air mixtures and result in a fire or dust explosion (including secondary explosions).</li> <li>▶ Avoid generating dust, particularly clouds of dust in a confined or unventilated space as dusts may form an explosive mixture with air, and any source of ignition, i.e. flame or spark, will cause fire or explosion. Dust clouds generated by the fine grinding of the solid are a particular hazard; accumulations of fine dust (420 micron or less) may burn rapidly and fiercely if ignited - particles exceeding this limit will generally not form flammable dust clouds; once initiated, however, larger particles up to 1400 microns diameter will contribute to the propagation of an explosion.</li> <li>Combustion products include:         <ul> <li>carbon dioxide (CO)</li> <li>carbon dioxide (CO2)</li> <li>hydrogen fluoride(HF)</li> <li>other pyrolysis products typical of burning organic material.</li> <li>CARE: Contamination of heated / molten liquid with water may cause violent steam explosion, with scattering of hot contents.</li> <li>▶ Polytetrafluoroethylene (PTFE) and related polyfluorinated polymers does not burn without an external flame.</li> <li>▶ WARNING: We ar neoprene gloves when handling refuse from fire where polytetrafluoroethylene (PTFE) was present.</li> </ul> </li> </ul> |

# SECTION 6 ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

See section 8

6.2. Environmental precautions

6.3. Methods and material for containment and cleaning up

Minor Spills

▶ Clean up all spills immediately.

Chemwatch: 9-553968 Page 4 of 10 Is sue Date: 22/06/2018 Version No: 2.2 Print Date: 23/08/2018

#### PTFE Additive Powder

|              | <ul> <li>Avoid contact with skin and eyes.</li> <li>Wear impervious gloves and safety glasses.</li> <li>Use dry clean up procedures and avoid generating dust.</li> </ul>   |
|--------------|---|
| Major Spills | <ul> <li>Clear area of personnel and move upwind.</li> <li>Alert Fire Brigade and tell them location and nature of hazard.</li> <li>Control personal contact with the substance, by using protective equipment and dust respirator.</li> <li>Prevent spillage from entering drains, sewers or water courses.</li> </ul> |

#### 6.4. Reference to other sections

Personal Protective Equipment advice is contained in Section 8 of the SDS.

#### SECTION 7 HANDLING AND STORAGE

Safe handling

#### 7.1. Precautions for safe handling

- ▶ The greatest potential for injury caused by molten materials occurs during purging of machinery (moulders, extruders etc.)
- ▶ It is essential that workers in the immediate area of the machinery wear eye and skin protection (such as full face, safety glasses, heat resistant gloves, overalls and safety boots) as protection from thermal burns.
- Fumes or vapours emitted from hot melted materials, during converting operations, may condense on overhead metal surfaces or exhaust ducts. The condensate may contain substances which are irritating or toxic. Avoid contact of that material with the skin.
- Limit all unnecessary personal contact.
- Wear protective clothing when risk of exposure occurs.
- ▶ Use in a well-ventilated area.
- ▶ Avoid contact with incompatible materials.
- ▶ Organic powders when finely divided over a range of concentrations regardless of particulate size or shape and suspended in air or some other oxidizing medium may form explosive dust-air mixtures and result in a fire or dust explosion (including secondary explosions)
- Minimise airborne dust and eliminate all ignition sources. Keep away from heat, hot surfaces, sparks, and flame.
- Establish good housekeeping practices.
- Remove dust accumulations on a regular basis by vacuuming or gentle sweeping to avoid creating dust clouds.

### Fire and explosion protection

See section 5

Other information

- ▶ Store in original containers.
- ▶ Keep containers securely sealed.
- Store in a cool, dry area protected from environmental extremes.
- ▶ Store away from incompatible materials and foodstuff containers

#### 7.2. Conditions for safe storage, including any incompatibilities

# Suitable container

- Lined metal can, lined metal pail/ can.
- Plastic pail.
- Polvliner drum.
- ▶ Packing as recommended by manufacturer.

# Storage incompatibility

Avoid contamination of water, foodstuffs, feed or seed. For saturated perfluorocarbons:

- Fatandard exidation-reduction potentials do not apply to PFCs. The materials are unaffected by electrochemical reactions and do not dissociate in aqueous media. ▶ They are essentially already fully oxidised and are unaffected by standard oxidizing agents such as permanganates, chromates, etc.
- The only known oxidation takes place only at high temperatures by thermal decomposition.
- Likewise, the materials are only reduced under extreme conditions, requiring reducing agents such as elemental sodium
- Avoid magnesium, aluminium and their alloys, brass and steel.

For polytetrafluoroethylene (PTFE) and other related polyfluorinated polymers:

Avoid storage with strong oxidising agents, tetrafluoroethylene, hexafluoroethylene, perfluoroisobutylene, carbonyl fluoride and hydrogen fluoride.

#### 7.3. Specific end use(s)

See section 1.2

#### SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

# 8.1. Control parameters

DERIVED NO EFFECT LEVEL (DNEL)

Not Available

PREDICTED NO EFFECT LEVEL (PNEC)

Not Available

OCCUPATIONAL EXPOSURE LIMITS (OEL)

# INGREDIENT DATA

| Source                      | Ingredient                  | Material name | TWA           | STEL   |           | Peak          |       | Notes         |
|-----------------------------|-----------------------------|---------------|---------------|--------|-----------|---------------|-------|---------------|
| Not Available               | Not Available               | Not Available | Not Available | Not Av | a ila ble | Not Available |       | Not Available |
| EMERGENCY LIMITS            |                             |               |               |        |           |               |       |               |
| Ingredient                  | Material name               |               | TEEL-1        |        | TEEL-2    |               | TEEL  | 3             |
| polyte tra fluoroe thyle ne | Polyte tra fluoroe thyle ne |               | 12 mg/m3      |        | 130 mg/m3 |               | 790 n | ng/m3         |

| Y | 0 | TOT II |  |
|---|---|--------|--|

#### Revised IDLH Ingredient Original IDLH polyte tra fluoroe thyle ne Not Available Not Available

#### 8.2. Exposure controls

8.2.1. Appropriate engineering | Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be

 Chemwatch: 9-553968
 Page 5 of 10
 Issue Date: 22/06/2018

 Version No: 2.2
 Print Date: 23/08/2018

#### PTFE Additive Powder

highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are: Process controls which involve changing the way a job activity or process is done to reduce the risk. Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. For molten materials: Provide mechanical ventilation; in general such ventilation should be provided at compounding/converting areas and at fabricating/filling work stations where the material is heated. Local exhaust ventilation should be used over and in the vicinity of machinery involved in controls handling the molten material. Keep dry!! Processing temperatures may be well above boiling point of water, so wet or damp material may cause a serious steam explosion if used in unvented equipment. For polytetrafluoroethylene (PTFE) and other related polyfluorinated polymers: In processes such as extrusion moulding, engineering controls should be designed to draw thermal degeneration products from the workers breathing zone. NOTE: When hydrogen fluoride is first detected continue to run equipment with the heat source to the polymer turned off. Ventilate the area and remove non-essential personnel from the area. In case of a major decomposition event evacuate all personnel immediately 8.2.2. Personal protection Safety glasses with side shields Chemical goggles. Eye and face protection Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Skin protection The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice. Personal hygiene is a key element of effective hand care. When handling hot materials wear heat resistant, elbow length gloves. Hands/feet protection Rubber gloves are not recommended when handling hot objects, materials Protective gloves eg. Leather gloves or gloves with Leather facing Experience indicates that the following polymers are suitable as glove materials for protection against undissolved, dry solids, where abrasive particles are not present. • polychloroprene. nitrile rubber. butyl rubber. Body protection See Other protection below When handling hot or molten liquids, wear trousers or overalls outside of boots, to avoid spills entering boots. Usually handled as molten liquid which requires worker thermal protection and increases hazard of vapour exposure. · CAUTION: Vapours may be irritating. No special equipment needed when handling small quantities. Other protection OTHERWISE: • Overalls. Barrier cream. · Eyewash unit.

# Respiratory protection

Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSIZ88 or national equivalent)

| Required Minimum Protection Factor | Half-Face Respirator | Full-Face Respirator | Powered Air Respirator |
|------------------------------------|----------------------|----------------------|------------------------|
| up to 10 x ES                      | A P1<br>Air-line *   | -                    | A PAPR-P1              |
| up to 50 x ES                      | Air-line **          | A P2                 | A PAPR-P2              |
| up to 100 x ES                     | -                    | AP3                  | -                      |
|                                    |                      | Air-line*            | -                      |
| 100+ x ES                          | -                    | Air-line ***         | A PAPR-P3              |

<sup>\* -</sup> Negative pressure demand \*\* - Continuous flow

 $A(All\ classes) = Organic\ vapours,\ B\ AUS\ or\ B1 = Acid\ gasses,\ B2 = Acid\ gas\ or\ hydrogen\ cyanide(HCN),\ B3 = Acid\ gas\ or\ hydrogen\ cyanide(HCN),\ E = Sulfur\ dioxide(SO2),\ G = Agricultural\ chemicals,\ K = Ammonia(NH3),\ Hg = Mercury,\ NO = Oxides\ of\ nitrogen,\ MB = Methyl\ bromide,\ AX = Low\ boiling\ point\ organic\ compounds (below\ 65\ degC)$ 

#### For molten materials:

- Respirators may be necessary when engineering and administrative controls do not adequately prevent exposures.
- The decision to use respiratory protection should be based on professional judgment that takes into account toxicity information, exposure measurement data, and frequency and likelihood of the worker's exposure ensure users are not subject to high thermal loads which may result in heat stress or distress due to personal protective equipment (powered, positive flow, full face apparatus may be an option).
- Published occupational exposure limits, where they exist, will assist in determining the adequacy of the selected respiratory protection. These may be government mandated or vendor recommended.
- Certified respirators will be useful for protecting workers from inhalation of particulates when properly selected and fit tested as part of a complete respiratory protection program.
- Use approved positive flow mask if significant quantities of dust becomes airborne.
- ▶ Try to avoid creating dust conditions.

PTFE Additive Powder

Issue Date: 22/06/2018
Print Date: 23/08/2018

See section 12

# SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

# 9.1. Information on basic physical and chemical properties

| Appearance Use may require material be molten. Molten or heated material may be compounded, moulded or extruded. |               |   |                |
|--|---------------|---|----------------|
| Physical state   | Solid         | Relative density (Water = 1)            | 2.140-2.20     |
| Odour  | Not Available | Partition coefficient n-octanol / water | Not Available  |
| Odour threshold  | Not Available | Auto-ignition temperature (°C)          | Not Available  |
| pH (as supplied)   | Not Available | Decomposition temperature               | Not Available  |
| Melting point / freezing point (°C)  | Not Available | Viscosity (cSt)                         | Not Available  |
| Initial boiling point and boiling range (°C)   | 320-342       | Molecular weight (g/mol)                | Not Available  |
| Flash point (°C)   | Not Available | Taste                                   | Not Available  |
| Evaporation rate   | Not Available | Explosive properties                    | Not Available  |
| Flammability   | Not Available | Oxidising properties                    | Not Available  |
| Upper Explosive Limit (%)  | Not Available | Surface Tension (dyn/cm or mN/m)        | Not Applicable |
| Lower Explosive Limit (%)  | Not Available | Volatile Component (% vol)              | Not Available  |
| Vapour pressure (kPa)  | Not Available | Gas group                               | Not Available  |
| Solubility in water (g/L)  | Immiscible    | pH as a solution (1%)                   | Not Available  |
| Vapour density (Air = 1)   | Not Available | VOC g/L                                 | Not Available  |

#### 9.2. Other information

Not Available

# SECTION 10 STABILITY AND REACTIVITY

| 10.1.Reactivity                          | See section 7.2   |
|--|---|
| 10.2. Chemical stability                 | Product is considered stable and hazardous polymerisation will not occur. |
| 10.3. Possibility of hazardous reactions | See section 7.2   |
| 10.4. Conditions to avoid                | See section 7.2   |
| 10.5. Incompatible materials             | See section 7.2   |
| 10.6. Hazardous decomposition products   | See section 5.3   |

# SECTION 11 TOXICOLOGICAL INFORMATION

# 11.1. Information on toxicological effects

| In h a le d  | The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified by EC Directives using animal models).  Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting. At temperatures of over 400 deg. C the polymer begins to decompose with the reaction becoming faster as temperature rises.  Fumes from burning materials containing PTFE irritate the upper airway and may be harmful if exposure is prolonged.  Overheated or burnt PTFE releases hydrogen fluoride (a highly irritating and corrosive gas) and small amounts of carbonyl fluoride (highly toxic).  Processing for an overly long time or processing at overly high temperatures may cause generation and release of highly irritating vapours, which irritate eyes, nose, throat, causing red itching eyes, coughing, sore throat.  Not normally a hazard due to non-volatile nature of product |
|--------------|--|
| Ingestion    | The material has not been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence.  High molecular weight material; on single acute exposure would be expected to pass through gastrointestinal tract with little change / absorption.  Occasionally accumulation of the solid material within the alimentary tract may result in formation of a bezoar (concretion), producing discomfort.   |
| Skin Contact | The material is not thought to produce adverse health effects or skin irritation following contact (as classified by EC Directives using animal models).  Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable gloves be used in an occupational setting.  Molten material is capable of causing burns.  Open cuts, abraded or irritated skin should not be exposed to this material  Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.   |
| Eye          | Although the material is not thought to be an irritant (as classified by EC Directives), direct contact with the eye may cause transient discomfort characterised by tearing or conjunctival redness (as with windburn). Slight abrasive damage may also result.   |
| Chronic      | Long-term exposure to the product is not thought to produce chronic effects adverse to the health (as classified by EC Directives using animal models); nevertheless exposure by all routes should be minimised as a matter of course.  Poly (tetrafluoroethylene) is used in the treatment for a number of urological disorders. Exposure of some experimental animals by local injection showed persistent chronic inflammatory reaction on histology of the sites taken. Repeated administration of 25% PFA (a derivative of PTFE) produced liver and testicular changes but subsequent studies did not reproduce these effects.  This material contains a substantial amount of polymer considered to be of low concern. These are classified under having MWs of between 1000 to 10000 with less than 25% of molecules with MWs under 1000 and less than 10% under 500; or having a molecular weight average of over 10000.   |

Chemwatch: 9-553968 Page 7 of 10 Issue Date: 22/06/2018 Version No: 2.2 Print Date: 23/08/2018

#### PTFE Additive Powder

|  | There has been some concern that this material can o   | cause cancer or mutations but there | is not enough data to make an assessment. |  |
|--|--|-------------------------------------|---|--|
|  |  |                                     |   |  |
| PTFE Additive Powder   | TOXICITY   | IRRITATION                          |   |  |
|  | Not Available  | Not Available                       |   |  |
|  | TOXICITY   | IRRITATION                          |   |  |
| polytetrafluoroethylene  | Oral (rat) LD50: 1250 mg/kg <sup>[2]</sup>   | Not Available                       |   |  |
|  |  |                                     |   |  |
| Legend:  | Value obtained from Europe ECHA Registered Sub-<br>otherwise specified data extracted from RTECS - Reg |                                     |   |  |
| -  |  |                                     |   |  |
| Perfluorinated compounds are potent peroxisome proliferators. The material may produce peroxisome proliferation. Peroxisomes are single, membrane limited organelles in the cytoplasm that are found in the cells of animals, plants, fungi, and protozoa. The substance is classified by IARC as Group 3: Not classifiable as to its carcinogenicity to humans. Evidence of carcinogenicity may be inadequate or limited in animal testing. |  |                                     |   |  |
|  |  |                                     |   |  |
| Acute Toxicity   | ×  | Carcinogenicity                     | 0   |  |
| Skin Irritation/Corrosion  | 0  | Reproductivity                      | 0   |  |
| Serious Eye Damage/Irritation  | 0  | STOT - Single Exposure              | 0   |  |
| Respiratory or Skin<br>sensitisation   | 0  | STOT - Repeated Exposure            | 0   |  |
| Mutagenicity   | ⊗  | As piration Hazard                  | 0   |  |

Legend:

X - Data available but does not fill the criteria for classification

✓ – Data available to make classification

#### Not Available to make classification

# SECTION 12 ECOLOGICAL INFORMATION

#### 12.1. Toxicity

| PTFE Additive Powder    | ENDPOINT<br>Not   | TEST DURATION (HR) | SPECIES       | VALUE<br>Not     | SOURCE<br>Not    |
|-------------------------|---|--------------------|---------------|------------------|------------------|
|                         | Available   | Not Available      | Not Available | Available        | Available        |
|                         | ENDPOINT  | TEST DURATION (HR) | SPECIES       | VALUE            | SOURCE           |
| polytetrafluoroethylene | Not<br>Available  | Not Available      | Not Available | Not<br>Available | Not<br>Available |
| Legend:                 | Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. EPIWIN Suite V3.12 (QSAR) - Aquatic Toxicity Data (Estimated) 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data |                    |               |                  |                  |

For polytetrafluoroethylene (PTFE) and other related polyfluorinated polymers:

Ecotoxicity is expected to be low based on the near zero water solubility of the polymer. Material is considered inert and is not expected to e biodegradable or toxic.

# 12.2. Persistence and degradability

| Ingredient                  | Persistence: Water/Soil | Persistence: Air |
|-----------------------------|-------------------------|------------------|
| polyte tra fluoroe thyle ne | HIGH                    | HIGH             |

#### 12.3. Bioaccumulative potential

| Ingredient                  | Bioaccumulation       |
|-----------------------------|-----------------------|
| polyte tra fluoroe thyle ne | LOW (LogKOW = 1.2142) |

# 12.4. Mobility in soil

| Ingredient                  | Mobility          |
|-----------------------------|-------------------|
| polyte tra fluoroe thyle ne | LOW (KOC = 106.8) |

#### 12.5.Results of PBT and vPvB assessment

|                         | P             | В             | T             |
|-------------------------|---------------|---------------|---------------|
| Relevant available data | Not Available | Not Available | Not Available |
| PBT Criteria fulfilled? | Not Available | Not Available | Not Available |

#### 12.6. Other adverse effects

No data available

Version No: 2.2 PTFE Additive Powder

Issue Date: 22/06/2018 Print Date: 23/08/2018

# SECTION 13 DISPOSAL CONSIDERATIONS

#### 13.1. Waste treatment methods

| Product / Packaging disposal | Do not allow wash water from cleaning or process equipment to enter drains.  It may be necessary to collect all wash water for treatment before disposal.  In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.  Where in doubt contact the responsible authority. |  |
|------------------------------|---|--|
| Waste treatment options      | Not Available   |  |
| Sewage disposal options      | Not Available   |  |

# SECTION 14 TRANSPORT INFORMATION

#### Labels Required

| Marine Pollutant | NO             |
|------------------|----------------|
| HAZCHEM          | Not Applicable |

# Land transport (ADR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

| 14.1. UN number                     | Not Applicable                                |  |
|-------------------------------------|---|--|
| 14.2. UN proper shipping name       | Not Applicable                                |  |
| 14.3. Transport<br>hazard class(es) | Class Not Applicable Subrisk Not Applicable   |  |
| 14.4. Packing group                 | Not Applicable                                |  |
| 14.5. Environmental hazard          | Not Applicable                                |  |
|                                     | Hazard identification (Kemler) Not Applicable |  |
| 14.6. Special precautions for user  | Classification code Not Applicable            |  |
|                                     | Hazard Label Not Applicable                   |  |
|                                     | Special provisions Not Applicable             |  |
|                                     | Limited quantity Not Applicable               |  |

# $Air\ transport\ (ICAO\text{-}IATA\ /\ DGR):\ NOT\ REGULATED\ FOR\ TRANSPORT\ OF\ DANGEROUS\ GOODS$

| 14.1. UN number                     | Not Applicable  |                |
|-------------------------------------|---|----------------|
| 14.2. UN proper shipping name       | Not Applicable  |                |
| 14.3. Transport<br>hazard class(es) | ICAO/IATA Class Not Applicable  ICAO / IATA Subrisk Not Applicable  ERG Code Not Applicable |                |
| 14.4. Packing group                 | Not Applicable  |                |
| 14.5. Environmental hazard          | Not Applicable  |                |
| 14.6. Special precautions for user  | Special provisions  | Not Applicable |
|                                     | Cargo Only Packing Instructions   | Not Applicable |
|                                     | Cargo Only Maximum Qty / Pack   | Not Applicable |
|                                     | Passenger and Cargo Packing Instructions  | Not Applicable |
|                                     | Passenger and Cargo Maximum Qty / Pack  | Not Applicable |
|                                     | Passenger and Cargo Limited Quantity Packing Instructions                                   | Not Applicable |
|                                     | Passenger and Cargo Limited Maximum Qty / Pack  | Not Applicable |

# Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

| 14.1. UN number                     | Not Applicable  |  |
|-------------------------------------|---|--|
| 14.2. UN proper shipping name       | Not Applicable  |  |
| 14.3. Transport<br>hazard class(es) | IMDG Class Not Applicable  IMDG Subrisk Not Applicable  |  |
| 14.4. Packing group                 | Not Applicable  |  |
| 14.5. Environmental hazard          | Not Applicable  |  |
| 14.6. Special precautions for user  | EMS Number   Not Applicable   Special provisions   Not Applicable   Limited Quantities   Not Applicable |  |

Chemwatch: 9-553968 Page 9 of 10 Version No: 2.2

PTFE Additive Powder

Inland waterways transport (ADN): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

| 14.1. UN number                     | Not Applicable  |  |
|-------------------------------------|---|--|
| 14.2. UN proper shipping name       | Not Applicable  |  |
| 14.3. Transport<br>hazard class(es) | Not Applicable Not Applicable   |  |
| 14.4. Packing group                 | Not Applicable  |  |
| 14.5. Environmental hazard          | Not Applicable  |  |
| 14.6. Special precautions for user  | Classification code Not Applicable Special provisions Not Applicable Limited quantity Not Applicable Equipment required Not Applicable Fire cones number Not Applicable |  |

14.7. Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

# SECTION 15 REGULATORY INFORMATION

15.1. Safety, health and environmental regulations / legislation specific for the substance or mixture

POLYTETRAFLUOROETHYLENE (9002-84-0) IS FOUND ON THE FOLLOWING REGULATORY LISTS

European Customs Inventory of Chemical Substances ECICS (English)  $International \ Agency \ for \ Research \ on \ Cancer \ (IARC) - Agents \ Classified \ by \ the \ IARC$ Monographs

This safety data sheet is in compliance with the following EU legislation and its adaptations - as far as applicable -: Directives 98/24/EC, -92/85/EEC, -94/33/EC, -2008/98/EC,  $-2010/75/EU; Commission\ Regulation\ (EU)\ 2015/830; Regulation\ (EC)\ No\ 1272/2008\ as\ updated\ through\ ATPs.$ 

#### 15.2. Chemical safety assessment

For further information please look at the Chemical Safety Assessment and Exposure Scenarios prepared by your Supply Chain if available.

#### ECHA SUMMARY

| Ingredient   | CAS number                             | Index No                       | ЕСНА Г  | Oossier                  |
|--|--|--------------------------------|---------|--------------------------|
| polyte tra fluoroe thyle ne  | 9002-84-0                              | Not Available                  | Not Ava | ila ble                  |
| Harmonis ation (C&L<br>Inventory)  | Hazard Class and Category Code(s)      | Pictograms Signal Word Code(s) |         | Hazard Statement Code(s) |
| 1  | Not Classified                         | Not Available                  |         | Not Available            |
| 2  | Eye Irrit. 2; Skin Irrit. 2; STOT SE 3 | GHS 07; Wng                    |         | H319; H315; H335; H332   |
| Harmonisation Code 1 = The most prevalent classification. Harmonisation Code 2 = The most severe classification. |  |                                |         |                          |

#### National Inventory Status

| National Inventory            | Status  |
|-------------------------------|---|
| Australia - AICS              | Y   |
| Canada - DSL                  | Y   |
| Canada - NDSL                 | N (polytetrafluoroethylene)   |
| China - IECSC                 | Y   |
| Europe - EINEC / ELINCS / NLP | N (polytetrafluoroethylene)   |
| Japan - ENCS                  | Y   |
| Korea - KECI                  | Y   |
| New Zealand - NZIoC           | Y   |
| Philippines - PICCS           | Y   |
| USA - TSCA                    | Y   |
| Legend:                       | Y = All ingredients are on the inventory N = Not determined or one or more ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets) |

# SECTION 16 OTHER INFORMATION

| Revision Date                   | 22/06/2018                        |  |
|---------------------------------|-----------------------------------|--|
| Initial Date                    | 22/06/2018                        |  |
| Full text Risk and Hazard codes |                                   |  |
| H315                            | Causes skin irritation.           |  |
| H319                            | Causes serious eye irritation.    |  |
| H332                            | Harmful if inhaled.               |  |
| H335                            | May cause respiratory irritation. |  |

Issue Date: 22/06/2018

Print Date: 23/08/2018

Chemwatch: 9-553968 Page 10 of 10 Issue Date: 22/06/2018 Version No: 2.2 Print Date: 23/08/2018

#### PTFE Additive Powder

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

For detailed advice on Personal Protective Equipment, refer to the following EU CEN Standards:

EN 166 Personal eye-protection

EN 340 Protective clothing

EN 374 Protective gloves against chemicals and micro-organisms

 $EN\ 13832\ Footwear\ protecting\ against\ chemicals$ 

EN 133 Respiratory protective devices

#### Definitions and abbreviations

PC-TWA: Permissible Concentration-Time Weighted Average PC-STEL: Permissible Concentration-Short Term Exposure Limit

IARC: International Agency for Research on Cancer

ACGIH: American Conference of Governmental Industrial Hygienists

STEL: Short Term Exposure Limit

TEEL: Temporary Emergency Exposure Limit.

IDLH: Immediately Dangerous to Life or Health Concentrations

OSF: Odour Safety Factor

NOAEL :No Observed Adverse Effect Level LOAEL: Lowest Observed Adverse Effect Level

TLV: Threshold Limit Value LOD: Limit Of Detection OTV: Odour Threshold Value BCF: BioConcentration Factors BEI: Biological Exposure Index

Powered by AuthorITe, from Chemwatch.